


Geckolighting® 30w LED Floodlight



Geckolighting® LED 30w Flood Light
 Robust lighting unit with polycarbonate lens (NO GLASS) for outside or inside applications including security and signage lighting, yards, open areas, sheds, mobile accommodation and display/feature lighting. Also cars, trucks and boats. **Gecko LED floodlights** deliver long life, high performance and minimum power usage. Low voltage 12 or 24 volt DC or High voltage 85-265VAC. Standard is Cool White (6000-6500K).



| Model Number | 70-FL30 (240VAC) 70-FL3012 (12VDC) 70-FL3024 (24VDC) |
|---------------------------------------|--|
| LED power: | 30W |
| Total power: | 33.4W |
| Input Voltage | 85-265VAC (70-FL30) DC24V (70-FL3024) DC12V (70-FL3012) |
| Frequency Range | 50/60Hz |
| Luminous flux: | 3,400lm |
| Power Factor(PF) | >0.95 |
| Total Harmonic Distortion (Thd) | <15% |
| Luminous efficiency: | >80-90lm/w |
| Light efficiency: | >90% |
| Operating temperature: | -30°C ~ +55°C |
| Color Temperature | CW - Cool white: 6,000K NW - Neutral White: 4,500K WW - Warm white: 3,000K |
| Color Index(CRI) | Ra>85 |
| Light Distribution Curve/Beam Pattern | Rectangular optical spot |
| Lighting angle: | Horizontal axis 120°, vertical axis 60° |
| Light Body& Lampshade | Aluminum Alloy And PC |
| IP Rating: | IP65 |
| Working Life | 50,000 Hrs |
| Dimensions – Width x Height x Depth: | 225mm(W) x 185mm(H) x 155mm(D) |
| Net Weight | 2Kgs |



| Distance (M) | Illuminance at a Distance | |
|--------------|---------------------------|-------------|
| | Center Beam LUX | Beam Width |
| 2.0M | 377.92 LUX | 4.5M 4.9M |
| 4.0M | 94.48 LUX | 9.0M 9.7M |
| 6.0M | 41.99 LUX | 13.5M 14.6M |
| 8.0M | 23.62 LUX | 18.0M 19.4M |
| 10.0M | 15.12 LUX | 22.5M 24.3M |
| 12.0M | 10.50 LUX | 27.0M 29.2M |

■ Vert. Spread: 96.7° ■ Horiz. Spread: 101.1°

Geckolighting
 Phone: (08) 9248 6205
 Fax: (08) 9248 3501
sales@geckolighting.com.au



www.geckolighting.com.au

