

Geckolighting® 30w LED Explosion Proof Floodlight



Geckolighting® LED 30W Explosion Proof Floodlight

Oil fields, Oil refineries, offshore oil platform, power plants, gas stations, oil tanks, wharf, tunnel, pumping stations etc. Zone I and Zone II hazardous locations, Zone 20, Zone 21, Zone 22 and IIA, IIB, IIC explosive gas atmosphere.

Features:

- Patented design.
- Low heat.
- Diecast aluminium housing with anti-static & anti-corrosive coating.
- Dust proof, waterproof.
- PC lens



Model Number	70-EX30
LED power:	30W
Input Voltage	95-265VAC or 24V DC
Frequency Range	50/60Hz
Luminous flux:	2,700lm
Power Factor(PF)	>0.95
Luminous efficiency:	>90lm/w
Light efficiency:	>90%
Operating temperature:	-30°C ~ +55°C
Color Temperature	Cool white: 5,000–6,500k Warm white: 2,700–4,000k
Color Index(CRI)	Ra>70
Beam Angle:	120°
Light Body& Lampshade	Aluminum Alloy and PC lens
Working Life	50,000 Hrs
Explosion Proof Grade:	Ex d IIB T5
Corrosion Proof Grade:	WF2
IP Rating:	IP66
Dimensions – Width x Height x Depth:	300mm x 300mm x 227mm
Certification:	CE, RoHS, CNEX, ATEX
Net Weight	6.5Kg

Geckolighting
 Phone: (08) 9248 6205
 Fax: (08) 9248 3501
 sales@geckolighting.com.au



www.geckolighting.com.au

